

HP 3D Printing materials portfolio selection guide¹



	HP 3D Printing Materials for HP Jet Fusion 5200 Series 3D Printing Solutions					HP 3D Printing Materials for HP Jet Fusion 4200 Series 3D Printing Solutions					HP 3D Printing Materials for HP Jet Fusion 500/300 Series 3D Printers
	HP 3D HR PA 11	HP 3D HR PA 12	HP 3D HR PA 12 GB	HP 3D HR PP enabled by BASF ²	BASF Ultrasint [®] TPU01 ²	HP 3D HR PA 11	HP 3D HR PA 12	HP 3D HR PA 12 GB	HP 3D HR TPA enabled by Evonik ³	ESTANE [®] 3D TPU M95A ³	HP 3D HR CB PA 12
	Rigid polymer				Elastomeric polymer	Rigid polymer			Elastomeric polymer		Rigid polymer
Stiffness	●	●	★	■	▲	●	●	★	▲	▲	●
Impact resistance	●	■	▲	■	★	●	■	▲	★	★	■
Elongation	●	■	▲	■	★	●	■	▲	★	★	■
Dimensional capability	●	★	●	■	■	●	★	●	■	■	■
Level of detail	★	●	●	■	■	★	●	●	●	■	●
Flat part	■	●	★	▲	■	■	●	★	■	■	●
Temperature resistance	▲	■	●	■	▲	▲	■	●	■	●	■
Chemical resistance ^{4,5}	●	●	n/a	★	■	●	●	n/a	▲	■	●
Low moisture absorption	▲	▲	▲	★	■	▲	▲	▲	■	■	▲
Lightweight	●	●	■	★	▲	●	●	■	● ⁶	▲	●

★ Best ● Good ■ Fair ▲ Not recommended

1. Based on internal HP testing, March 2020. For testing methodology and results, see hp.com/go/3Dprintingmaterialswhitepapers. Please consult your local sales representative for more information.

2. Available for HP Jet Fusion 5200 Series 3D Printing Solutions.

3. Available for HP Jet Fusion 4200 Series 3D Printing Solutions.

4. For HP 3D High Reusability PA 11, PA 12, and CB PA 12, based on internal HP testing, June 2017. Tested with diluted alkalis, concentrated alkalis, chlorine salts, alcohol, ester, ethers, ketones, aliphatic hydrocarbons, unleaded petrol, motor oil, aromatic hydrocarbons, toluene, and DOT 3 brake fluid. For HP 3D High Reusability PP enabled by BASF, based on internal HP testing, May 2020, with tests for mechanical property retention, dimensional stability, and weight change after 7- and 30-day immersion with acids, bases, organic solvents, and aqueous solutions. For BASF Ultrasint[®] TPU01, based on testing by BASF, April 2020, according to ASTM D471 for select IRM oils and Fuel A.

5. For HP 3D High Reusability PP enabled by BASF, based on internal HP testing, May 2020, with tests for mechanical property retention, dimensional stability, and weight change after 7- and 30-day immersion with acids, bases, organic solvents, and aqueous solutions.

6. Based on published specifications as of September, 2020. HP Jet Fusion 3D Printing Solutions using HP 3D High Reusability TPA enabled by Evonik provide up to 17% lower printed part weight when compared to common powder-based thermoplastic elastomers printed under similar conditions.

